

DATASHEET

19" Network Cabinet PRO 24U, 800x1000 mm, RAL7035



General data

19" network cabinet according to DIN41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, dismountable

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Contrariwise numbering of rack units at the 19" profiles

Front door with window of certified safety glass (thickness 5 mm)

Front door with 3-point turning handle (up to 24U 1-point), lockable, incl. profile half-cylinder acc. to DIN18252 / EN 1303

Profile half-cylinder exchangeable by customer (30/10 mm)

Rear door steel, 1-part, shortened, with 2 x latch locking (lock equal to door lock), 3U panel for cable entry below (690 x 67 mm)

Door stop for front and rear door possible left- or right-sided

Detachable side walls with 2 x latch locking (lock equal to the door lock)

Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X)

Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable entry only rear

Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules

Internal earthing of all cabinet sections

Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 2 x M5 + 2 x 8 mm)

Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

This datasheet was created automatically on 23-07-2024 . Technical changes reserved.

DATASHEET

19" Network Cabinet PRO 24U, 800x1000 mm, RAL7035

Paint finish RAL7035, light grey

Protection degree IP20

Included accessories: 1 x brush, 1 x set of captive nuts (PU 20 pcs.), earthing bar and earthing cables, 4 x levelling feet M12, 2 x key

Delivery in transport packaging on disposable pallet

Allgemeine Daten	
With front door	True
Type of ventilation	Passive
With backside door	True
Surface finishing	Powder coating
Number of cartons	1
With roof plate	True
Type of back door	Steel perforated 1-part
With sidewall	True
Mounting level	Front and rear
With socket	False
Model	With permanent frame
With earthing	True
Type of profile rail	Crank
Type of front door	Glass door 1-part

General data	
Modular spacing	482.6 mm (19 inch)
Demountable	True
Cabinet Series	PRO
Material	steel
Degree of protection	IP20

Available variants									
ArtNr.	Bezeichnung	Colour Depth		Max. Load Capacity	Number of height units	Width	Höhe	RAL-Nummer	Anzahl der Türen
PRO-2480GR.G1SV	19" Network Cabinet PRO 24U, 800x1000 mm, RAL7035	grey	1000 mm	-	24 U	800 mm	1163 mm	7035	2
PRO-2780GR.G1SV	19" Network Cabinet PRO 27U, 800x1000 mm, RAL7035	grey	1000 mm	-	27 U	800 mm	1297 mm	7035	2

This datasheet was created automatically on 23-07-2024 . Technical changes reserved.

DATASHEET

19" Network Cabinet PRO 24U, 800x1000 mm, RAL7035

PRO-3380GR.G1SV	19" Network Cabinet PRO 33U, 800x1000 mm, RAL7035	grey	1000 mm	1360 kg	33 U	800 mm	1563 mm	7035	2
PRO-3380TS.G1SV	19" Network Cabinet PRO 33U, 800x1000 mm, RAL9005	black	1000 mm	-	33 U	800 mm	1563 mm	9005	2
PRO-4280GR.G1SV	Network Cabinet PRO 42U, 800x1000 mm, RAL7035	grey	1000 mm	-	42 U	800 mm	1963 mm	7035	2
PRO-4280TS.G1SV	Network Cabinet PRO 42U, 800x1000 mm, RAL9005	black	1000 mm	-	42 U	800 mm	1963 mm	9005	2
PRO-4780GR.G1SV	Network Cabinet PRO 47U, 800x1000 mm, RAL7035	grey	1000 mm	-	47 U	800 mm	2186 mm	7035	2
PRO-4780TS.G1SV	Network Cabinet PRO 47U, 800x1000 mm, RAL9005	black	1000 mm	-	47 U	800 mm	2186 mm	9005	2

This datasheet was created automatically on 23-07-2024 . Technical changes reserved.

