

LogiLink®



4K 1x4 HDMI™ Splitter

Downscale, 4K/60 Hz

Art. No.: HD0037

This 4K HDMI Splitter with HDCP 2.2 is an advanced solution for splitting a single HDMI input to four HDMI outputs. It provides high performance audio and video output up to Ultra HD 4K@60 Hz resolution and delivers up to 18 Gbps of bandwidth, ensuring the best 4K picture quality.

Features:


- » Connects one HDMI source to four HDMI displays at the same time
- » Ultra slim design
- » Resolution up to UHD 4K@60 Hz (YUV 4:4:4) and Full 3D
- » Bandwidth: 6 Gbps/600 MHz per Channel (18 Gbps total)
- » Supports HDCP 2.2
- » Supports DDC, HDR, CEC and Downscale function
- » Supports 12bit per channel (36bit all channels) deep color
- » Supports uncompressed audio such as LPCM
- » Supports compressed audio such as DTS, Dolby Digital (including DTS-HD Master Audio™ and Dolby TrueHD)

Front




- (a) Power LED
- (b) HDMI output 1-4 LED indicator
- (c) USB DC 5V input
- (d) HDMI output 1-4 port
- (e) HDMI input port

Back



Compose Downscaler: Get lowest audio format of the outputs, and compose downscale of video. Downscale function means the product can downscale the input 4K resolution to 1080p by the FHD (1080p) displays and 4K resolution to the 4K displays simultaneously.



RoHS
compliant



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

Specifications:

Input Port	1x HDMI-A female
Output Ports	4x HDMI-A female
HDMI Version	2.0
HDCP Version	2.2
Output Resolution	480i/60 Hz, 576i/50 Hz, 1080i/50/60 Hz, 480p/60 Hz, 576p/50 Hz, 720p/50/60 Hz, 1080p/24/25/30/50/60 Hz, 4K@24/25/30 Hz, 4K@50/60 Hz 4:4:4
Video Bandwidth	6 Gbps/600 MHz
CEC (Consumer Electronics Control)	Yes
DDC (Display Data Channel)	Yes
HDR (High-Dynamic Range)	Yes
LED Indicator	Yes
Chassis Material	ABS
3D Supporting	Yes
Power Consumption	5 W max.
Uncompressed Audio	LPCM 7.1
Compressed Audio	DTS, Dolby Digital, DTS-HD Master Audio™, Dolby TrueHD
Operating Temperature	0°C–70°C
Operating Humidity	10%–85% RH (no condensation)
Storage Temperature	-10°C–80°C
Storage Humidity	5%–90% RH (no condensation)
Dimensions	13.3x5.9x1.7 cm
Weight	0.085 kg

Package Contents:

- » 1x 4K 1x4 HDMI Splitter
- » 1x USB Charging Cable
- » 1x User Manual

Package Information:

- » Packing Dimension: 160x107x50 mm
- » Packing Weight: 0.18 kg
- » Carton Dimension: 575x255x345 mm
- » Carton Q'ty: 40 pcs
- » Carton Weight: 7.9 kg



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



Made in China