



Bosch Serie 4 SMS4HMI07E dishwasher Freestanding 14 place settings D

Brand : Bosch

Product family: Serie 4

Product code: SMS4HMI07E

Product name : SMS4HMI07E

Bosch Serie 4 SMS4HMI07E. Appliance placement: Freestanding, Product size: Full size (60 cm), Door colour: Stainless steel. Number of place settings: 14 place settings, Noise emission class: B, Noise level: 42 dB. Feet adjustment: 2 cm, Apps supported: Bosch Home Connect. Energy efficiency class: D, Water consumption per cycle: 9 L, Energy consumption per 100 cycles: 85 kWh. Width: 600 mm, Depth: 600 mm, Height: 845 mm



Design		Performance	
Appliance placement *	Freestanding	Half-load	✓
Product size *	Full size (60 cm)	Self-cleaning	✓
Custom panel-ready *	✗	Ergonomics	
Door colour *	Stainless steel	Dosage assistant	✓
Control panel colour	Silver	Self-cleaning filter	✓
Control type	Touch	Child lock	✓
Built-in display *	✓	Adjustable feet	✓
Built-in water softener	✓	Feet adjustment	2 cm
Cord length	1.75 m	Remaining time indication	✓
Inlet hose length	1.9 m	Salt indicator	✓
Outlet hose length	1.65 m	Rinse aid indicator	✓
Upper basket adjustable height	✓	Apps supported	Bosch Home Connect
Upper basket adjustable height levels	3	Wi-Fi controlled	✓
Cutlery compartment type	Drawer	Power	
Cutlery basket type	Bosch VarioDrawer	Energy efficiency scale	A to G
Tub material	Stainless steel	Energy efficiency class *	D
Performance		Energy consumption per cycle	0.849 kWh
Noise level *	42 dB	Water consumption per cycle *	9 L
Dishwashing programs *	Auto 45-65°C, Eco 50°C, Favorite, Intensive 70°C, Pre-rinse, Quick 65°C, Silent 50°C	Energy consumption per 100 cycles *	85 kWh
Drying system	Heat exchanger	Connected load	2400 W
Number of place settings *	14 place settings	AC input voltage	220 - 240 V
Number of washing programs *	6	AC input frequency	50 - 60 Hz
Noise emission class *	B	Current	10 A
Temperature (max) *	70 °C	Weight & dimensions	
Maximum hot water supply temperature	60 °C	Depth	600 mm
Cycle time *	270 min	Height	845 mm
		Weight	50.6 kg

Performance		Weight & dimensions	
Delayed start timer	✓	Depth with door open	115.5 cm
Delay start (max)	24 h	Height under worktop	3 cm
AquaStop function *	✓	Width *	600 mm
AquaSensor function	✓	Packaging data	
Extra dry	✓	Package width	655 mm
Overflow protection *	✓	Package depth	670 mm
		Package height	875 mm
		Package weight	52.1 kg



4242005386598

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-MAY-2024. Prints or copies of Information are only valid on the printed Publication date