



Power your play with the curved G-Master GC2784HSU-B1 featuring 240Hz and 0.7ms response time

Experience absolute speed with a panoramic edge.

In high-stakes gaming, the slightest delay or motion blur can break your concentration and cost you the win. The G-Master GC2784HSU-B1 eliminates these barriers, pairing a satisfying 240Hz refresh rate with a 0.7ms MPRT response time for unparalleled motion clarity. Its 1500R curved VA panel delivers sharp FHD resolution, optimized for high-frame-rate performance, while pulling you deeper into the world and offering a superior static contrast ratio for the black depth. Supported by Adaptive Sync, this monitor delivers a seamless, high-velocity experience that ensures you see every movement first and react with perfect precision.

Available also with height adjustable stand : [G-Master GCB2784HSU-B1](#)



CURVED DESIGN 1500R

The 1500R curvature of the screen guarantees a realistic and comfortable viewing experience allowing you to really immerse yourself in the game.



VA PANEL TECHNOLOGY

Guaranteeing excellent contrast ratio making all the nuances between the light and dark colours clearly visible.

01 DISPLAY CHARACTERISTICS

Design	curved
Diagonal	27", 68,6cm
Panel	VA
Curved	1500R
Native resolution	1920 x 1080 @240Hz
Aspect ratio	16:9
Panel brightness	350 cd/m ²
Static contrast	4000:1
Advanced contrast	80M:1
Response time (MPRT)	0,7ms
Viewing zone	horizontal/vertical: horizontal°/vertical 178°, right/left: 0°/0°, up/down: 0°/0°
Colour support	16.7mIn 8bit (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 300kHz
Viewable area W x H	597.9 x 336.3mm
Pixel pitch	0.311mm
Colour	black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (ver. 2.1 TMDS) DisplayPort x1 (ver. 1.4)
USB HUB	x2 (v. 2.0; 5V, 500mA)
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync Premium - 1920 x 1080 @48-240Hz
HDR	HDR10
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power Indicator, Joystick: Power / Menu (Center), Up / Signal Select, Down, Left / i-Style Colour / Night Mode / Blue Light Reducer, Right / Volume
User controls	picture adjust (contrast, brightness, OD, HDR, FreeSync Premium, ACR, Night Mode, Blue Light Reducer, Motion Blur Reduction, Gamma), input select, audio settings (volume, mute), store user settings (user modes), colour settings (6-axis, colour temperature, user preset, black tuner), image adjust (i-Style Colour, x-res technology, sharpness, HDMI range, direct drive mode, video mode adjust), language, setup menu (OSD horizontal position, OSD vertical position, OSD time, opening logo, power LED, DDC/CI control, USB charge, PIP/PBP), display information, reset
Speakers	2 x 2W

04 MECHANICAL

Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power (1.85m), USB (1.5m), HDMI (1.85m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC AC - 100V, 240/V, 50Hz
Power usage	21W default, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations	CB, CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	E

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	610,5 x 466,5 x 192,5mm
Box dimensions W x H x D	693 x 439 x 163mm
Weight (without box)	4kg
Weight (with box)	6,54kg
EAN code	4948570127580

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED