



EIZO FlexScan EV2781 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED White

Brand : EIZO

Product family: FlexScan

Product code: EV2781-WT

Product name : EV2781

- 70 Watt Power Delivery
 - High Resolution for Efficient Multi-Tasking
 - Versatile Stand for Optimal Positioning
 - Portrait Mode for Vertical Viewing
 - Streamlined Mouse Operation
- 27", IPS QHD (2560 x 1440), 109 ppi, 350 cd/m², 1000: 1, 5 ms, sRGB, 60 Hz, USB Type-C, HDMI, DisplayPort, 18 W

EIZO FlexScan EV2781. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: White



Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	HDMI *	✓
Display resolution *	2560 x 1440 pixels	HDMI ports quantity	1
HD type *	Quad HD	DisplayPorts quantity	1
Native aspect ratio *	16:9	Headphone out *	✓
Display technology *	LED	Headphone outputs	1
Panel type *	IPS	Headphone connectivity	3.5 mm
Backlight type	LED	HDCP	✓
Touchscreen *	✗	Ergonomics	
Display brightness (typical)	350 cd/m ²	VESA mounting *	✓
Response time	5 ms	Panel mounting interface	100 x 100 mm
Screen shape *	Flat	Cable lock slot *	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1440	Cable lock slot type	Kensington
		Height adjustment *	✓
		Height adjustment	17.7 cm
		Pivot	✓
Contrast ratio (typical) *	1000:1	Pivot angle	-90 - 90°
Maximum refresh rate *	60 Hz	Swivelling	✓
Viewing angle, horizontal	178°	Swivel angle range	0 - 344°
Viewing angle, vertical	178°	Tilt adjustment	✓
Display number of colours *	16.7 million colours	Tilt angle range	-5 - 35°
Pixel pitch	0.233 x 0.233 mm	On Screen Display (OSD)	✓
Pixel density	109 ppi	On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Swedish
Horizontal scan range	31 - 89 kHz	Power	
Vertical scan range	59 - 61 Hz	Energy efficiency class (SDR) *	D
Viewable size, horizontal	59.7 cm	Energy consumption (SDR) per 1000 hours *	17 kWh
Viewable size, vertical	33.6 cm	Power consumption (typical) *	18 W
Display diagonal (metric)	68.5 cm	Power consumption (standby) *	0.5 W
RGB colour space	sRGB		

Performance		Power	
NVIDIA G-SYNC *	✗	Power consumption (max)	153 W
AMD FreeSync *	✗	AC input voltage	100 - 240 V
Multimedia		AC input frequency	50 - 60 Hz
Built-in speaker(s) *	✓	Energy efficiency scale	A to G
Built-in camera *	✗	Operational conditions	
Number of speakers	2	Operating temperature (T-T)	5 - 35 °C
RMS rated power	2 W	Operating relative humidity (H-H)	20 - 80%
Design		Packaging content	
Market positioning *	Business	Cables included	AC, USB Type-A to USB Type-C
Product colour *	White	Quick start guide	✓
Certification	CE, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 9, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTUVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC, EAC	Weight & dimensions	
		Width (with stand)	611 mm
		Depth (with stand)	230 mm
		Height (with stand)	369 mm
		Weight (with stand)	8.5 kg
		Width (without stand)	611 mm
		Depth (without stand)	56 mm
		Height (without stand)	357 mm
		Weight (without stand)	5.7 kg
Ports & interfaces		Sustainability	
Built-in USB hub *	✓	Sustainability compliance	✓
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Sustainability certificates	CB, CCC, CE, China RoHS, EAC, ENERGY STAR, EPEAT Climate +, EPEAT Gold, Federal Communications Commission (FCC), ICES, PSE, RCM, RoHS, TUV, VCCI, WEEE, cTUVus
USB upstream port type	USB Type-C		
Number of upstream ports	1	European Product Registry for Energy Labelling (EPREL) code	1103462
Number of USB Type-C upstream ports quantity	1		
USB Type-A downstream ports quantity	4		
USB Type-C DisplayPort Alternate Mode	✓		
USB Power Delivery	✓		
USB Power Delivery up to	70 W		



4995047063445

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-MAY-2024. Prints or copies of Information are only valid on the printed Publication date