



EZVIZ CS-E6 security camera Bulb IP security camera Indoor 2880 x 1620 pixels Desk

Brand : EZVIZ

Product code: CS-E6

Product name : CS-E6

EZVIZ CS-E6. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wireless. Mounting type: Desk, Product colour: Black, Grey, Form factor: Bulb. Lens viewing angle, horizontal: 87°, Lens viewing angle, vertical: 48°, Lens viewing angle, diagonal: 103°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Night vision distance: 10 m



Performance		Audio	
Type *	IP security camera	Audio system	2-way
Placement supported *	Indoor	Network	
Connectivity technology *	Wireless	Ethernet LAN *	✓
Wide Dynamic Range (WDR)	✓	Ethernet interface type	Fast Ethernet
Day/night mode	✓	Wi-Fi *	✓
Operating frequency	2400 - 5835 MHz	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Dynamic range	80 dB	Channel bandwidth	40 MHz
Certification	UL/CE/RoHS/WEEE/REACH/FCC/UKCA	Storage	
Design		Built-in HDD *	✗
Form factor *	Bulb	Card reader integrated	✓
Mounting type *	Desk	Compatible memory cards	MicroSD (TransFlash)
Product colour *	Black, Grey	Maximum memory card size	512 GB
Camera		Ports & interfaces	
Lens viewing angle, horizontal	87°	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, vertical	48°	Security	
Lens viewing angle, diagonal	103°	Password protection	✓
Tilt angle range	0 - 75°	Security algorithms	WPA, WPA2-PSK
Pan range	0 - 350°	Anti-flicker	✓
Image sensor		Mirror	✓
Number of sensors	1	Digital watermark	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Power	
Sensor type *	CMOS	Power source type *	DC
Lens system		Power consumption (max)	8 W
Zoom capability	✓	DC output voltage	5
Night vision		DC output current	2 A
Night vision *	✓	Operational conditions	
Night vision distance	10 m	Operating temperature (T-T)	-10 - 45 °C
Video		Operating relative humidity (H-H)	0 - 95%
Maximum resolution *	2880 x 1620 pixels	Weight & dimensions	
Total megapixels *	5 MP		
Video compression formats	H.264, H.265		

Video		Weight & dimensions	
Frame rate	25 fps	Width	95.8 mm
Noise reduction	✓	Depth	95.8 mm
Noise reduction technology	3D noise reduction	Height	90.6 mm
Image quality adjustment	DNR	Weight	252 g
Back Light Compensation (BLC)	✓	Package width	116 mm
		Package depth	116 mm
		Package height	164 mm
		Package weight	513 g
		Packaging content	
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-MAY-2024. Prints or copies of Information are only valid on the printed Publication date