

Technical Specifications

APC Easy UPS SRV RM 10000VA 230V with External Battery Pack,with RailKit | SRV10KRILRK | Downloaded on 05/06/2019 (EST)



APC Easy UPS SRV RM 10000VA 230V with External Battery Pack,with RailKit

SRV10KRILRK

Call for More Information 800 11 62 900

- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions
- Includes: CD with software, USB cable, User Manual

Output

Output power capacity	10.0kWatts / 10.0kVA
Max Configurable Power (Watts)	10.0kWatts / 10.0kVA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave

Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	Hard Wire 3-wire
Other Input Voltages	220, 240

Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	600Joules
---------------------	-----------

Physical

Maximum Height	173MM, 17.3CM
----------------	---------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Easy UPS SRV RM 10000VA 230V with External Battery Pack,with RailKit | SRV10KRILRK | Downloaded on 05/06/2019 (EST)

Physical

Maximum Width	438MM, 43.8CM
Maximum Depth	710MM, 71.0CM
Net Weight	69.0KG
Shipping weight	79.0KG

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-14763.6meters

Conformance

Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.