

Vertiv Liebert GXE3-3000IRT2UXL uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 2700 W 9 AC outlet(s)

Brand : Vertiv

Product family: Liebert

Product code:
GXE3-3000IRT2UXL

Product name :
GXE3-3000IRT2UXL

- Reliable online double-conversion topology
 - High output power factor (0.9) to protect more loads
 - Hot-swappable user replaceable internal batteries without load shutdown
 - Remote management and server shutdown with the optional network management card
 - Fast recharge time (<4hrs @90%) and scalable runtime capabilities in rack/tower models
- Liebert GXE UPS 3000VA/2700W 230V Online Double Conversion Rack/Tower | Lead Acid VRLA Battery | Optional battery cabinets (GXE3-3000IRT2UXL)
- Vertiv Liebert GXE3-3000IRT2UXL. UPS topology: Double-conversion (Online), Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 3.3 min, Typical backup time at half load: 9.5 min. Form factor: Rackmount/Tower, Product colour: Grey, Rack capacity: 2U. Compliance certificates: CB, CE, RCM, REACH, RoHS, UKCA, WEEE



Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at half load	9.5 min
Output power capacity *	3 kVA	Battery life (max)	5 year(s)
Output power *	2700 W	Battery recharge time	4 h
Waveform *	Pure sine	Design	
Input operation voltage (min) *	110 V	Form factor *	Rackmount/Tower
Input operation voltage (max) *	290 V	Rack capacity	2U
Input frequency *	40 - 70 Hz	Product colour *	Grey
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	Operational conditions	
Surge energy rating	600 J	Operating temperature (T-T)	0 - 40 °C
Efficiency (On-line mode)	91%	Storage temperature (T-T)	-20 - 50 °C
Efficiency (ECO mode)	96%	Operating relative humidity (H-H)	5 - 90%
EMI/RFI noise filtering	✓	Operating altitude	0 - 2000 m
Noise level	53 dB	Certificates	
Ports & interfaces		Compliance certificates	CB, CE, RCM, REACH, RoHS, UKCA, WEEE
AC outlet types	C13 coupler, C19 coupler	Packaging content	
AC outlets quantity	9 AC outlet(s)	Cables included	Input power cable, Output power cable, USB cable
USB port	✓	Quick installation guide	✓
Emergency Power Off (EPO) connector	✓	Sustainability	
Battery		Sustainability compliance	✓
Battery technology	Sealed Lead Acid (VRLA)	Weight & dimensions	
Number of batteries supported	6	Width	438 mm
Typical backup time at full load	3.3 min	Depth	630 mm
		Height	86 mm

Weight & dimensions	
Weight	31.5 kg
Packaging data	
Package width	790 mm
Package depth	600 mm
Package height	235 mm
Package weight	34.2 kg



0767041034424



767041034424

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.