

Intellinet Cat6a 10G Shielded Toolless RJ45 Modular Field Termination Plug, For Easy and Quick High-quality Cable Assembly in the Field, STP, for Solid & Stranded Wire, Gold-plated Contacts, Metal Housing

Brand : Intellinet

Product code: 790796

Product name : Cat6a 10G Shielded Toolless RJ45 Modular Field Termination Plug, For Easy and Quick High-quality Cable Assembly in the Field, STP, for Solid & Stranded Wire, Gold-plated Contacts, Metal Housing

Cat6a 10G Shielded Toolless RJ45 Modular Field Termination Plug, For Easy and Quick High-quality Cable Assembly in the Field, STP, for Solid & Stranded Wire, Gold-plated Contacts, Metal Housing

[Intellinet Cat6a 10G Shielded Toolless RJ45 Modular Field Termination Plug, For Easy and Quick High-quality Cable Assembly in the Field, STP, for Solid & Stranded Wire, Gold-plated Contacts, Metal Housing:](#)

Field-installable Cat6a STP RJ45 Modular Plug for easy, fast and tool-free high-quality cable assembly

The Cat6a 10G Shielded Toolless RJ45 Modular Field Termination Plug from Intellinet Network Solutions is designed for time-saving, high-quality cable terminations, even when out in the field for such devices as security cameras, industrial electronics and more. Without any special tools, the cable can be assembled within two minutes. This plug is suitable for both stranded and solid conductor cables for high-performance network applications up to 10GBase-T with PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE. For maximum signal integrity, it is equipped with gold-plated contacts and 360° STP shielding.

Features		Features	
Connector(s) *	RJ45	Certification	CE RoHS FCC ISO/IEC 11801 IEC 60603-7-51 Cat5 (ANSI/TIA/EIA-568-D) Cat5e (TIA/EIA-568-D) Cat6 (ANSI/TIA-568-D) Cat6a (ANSI/TIA-568-D)
Connector gender	Male		
Connector form factor	Straight		
Product colour *	Stainless steel		
Cable standard	Cat6a	Operational conditions	
Cable shielding	U/FTP (STP)	Operating temperature (T-T)	-10 - 60 °C
Connector contacts plating	Gold	Storage temperature (T-T)	-40 - 70 °C
Contact resistance	20 mΩ	Weight & dimensions	
Current	1.5 A	Weight	20 g
		Width	15 mm
		Depth	41 mm
		Height	18 mm



0766623790796



766623790796

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.