

Philips 275S9JML/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black

Brand : Philips

Product code: 275S9JML/00

Product name : 275S9JML/00

Business Monitor 275S9JML LCD monitor

Philips 275S9JML/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black:

Our S Line monitor delivers business efficiency. Features like Flicker-free and LowBlue mode make work easy on the eyes and increase your productivity.

Philips 275S9JML/00. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Tilt angle range	-5 - 25°
Display resolution *	2560 x 1440 pixels	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
HD type *	Quad HD		
Native aspect ratio *	16:9		
Display technology *	LCD	Plug and Play	✓
Panel type *	VA	LED indicators	Operation, Stand-by
LED backlight	✓	Power	
Backlight type	W-LED	Energy efficiency class (SDR) *	F
Display brightness (typical)	300 cd/m²	Energy efficiency class (HDR) *	Not available
Response time *	4 ms	Energy consumption (SDR) per 1000 hours *	26 kWh
Anti-glare screen	✓	Power consumption (typical) *	19.6 W
Screen shape *	Flat	Power consumption (standby) *	0.3 W
Contrast ratio (typical) *	4000:1	Power consumption (off)	0.3 W
Maximum refresh rate *	75 Hz	Power consumption (PowerSave)	15 W
Viewing angle, horizontal	178°	AC input voltage	100 - 240 V
Viewing angle, vertical	178°	AC input frequency	50 - 60 Hz
Display number of colours *	16.7 million colours	Power supply type	Internal
Pixel pitch	0.2331 x 0.2331 mm	Energy efficiency scale	A to G
Pixel density	108.79 ppi	Operational conditions	
Horizontal scan range	30 - 114 kHz	Operating temperature (T-T)	0 - 40 °C
Vertical scan range	48 - 75 Hz	Storage temperature (T-T)	-20 - 60 °C
Viewable size, horizontal	59.7 cm	Operating relative humidity (H-H)	20 - 80%
Viewable size, vertical	33.6 cm	Operating altitude	0 - 3658 m
Display diagonal (metric)	68.5 cm	Non-operating altitude	0 - 12192 m
DDC/CI	✓		
Haze rate	25%		
Surface hardness	3H		
Colour depth	8 bit		
sRGB coverage (typical)	119%		

Display		Weight & dimensions	
NTSC coverage (typical)	97%	Width (with stand)	613 mm
Display sRGB	✓	Depth (with stand)	205 mm
Performance		Height (with stand)	525 mm
VESA Adaptive Sync support	✓	Weight (with stand)	5.6 kg
Component video sync	Separate Sync	Width (without stand)	613 mm
Flicker-free technology	✓	Depth (without stand)	56 mm
Multimedia		Height (without stand)	367 mm
Number of speakers	2	Weight (without stand)	3.84 kg
Built-in speaker(s) *	✓	Packaging data	
Built-in camera *	✗	Package width	780 mm
Design		Package depth	161 mm
Market positioning *	Business	Package height	445 mm
Product colour *	Black	Package weight	8.2 kg
Front bezel colour	Black	Packaging content	
Feet colour	Black	Stand included	✓
Ports & interfaces		Manual	✓
Built-in USB hub *	✓	Bundled software	SmartControl
USB upstream port type	USB Type-B	Sustainability	
Audio output	✓	Doesn't contain	Mercury, PVC/BFR
HDCP	✓	Other features	
HDCP version	1.4	Exterior finish type	Textured
Charging port type	USB Type-A	Picture enhancement	SmartImage
Ergonomics		Regulatory Approvals	CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003; TUV Ergo; TUV/GS
VESA mounting *	✓	EasyRead mode	✓
Panel mounting interface	100 x 100 mm	LowBlue mode	✓
Cable lock slot *	✓	Mean time between failures (MTBF)	70000 h
Cable lock slot type	Kensington	Recycling data	
Height adjustment *	✓	Recyclable packaging material	100%
Adjustable height (max)	13 cm	Post-consumer recycled plastic	85%
Pivot angle	-90 - 90°		
Swivel angle range	-180 - 180°		
Tilt adjustment	✓		



8712581801168

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.