

KYOCERA ECOSYS M8130cidn Laser A3 9600 x 600 DPI 30 ppm

Brand : KYOCERA

Product family: ECOSYS

Product code:
870B61102P33NL3

Product name : M8130cidn

KYOCERA ECOSYS M8130cidn. Print technology: Laser, Printing: Colour printing, Maximum resolution: 9600 x 600 DPI, Print speed (colour, normal quality, A4/US Letter): 30 ppm. Copying: Colour copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Maximum ISO A-series paper size: A3. Direct printing. Product colour: Black, White

Printing		Paper handling	
Duplex printing mode	Auto	Multi-purpose tray media types	Legal, Letter, Plain paper
Print resolution colour	1200 x 1200 DPI	ISO A-series sizes (A0...A9) *	A3, A4, A5, A6
Print resolution black	1200 x 1200 DPI	ISO B-series sizes (B0...B9)	B5
Print technology *	Laser	Non-ISO print media sizes	Folio, Ledger (media size), Letter
Printing *	Colour printing	Custom media width	98 - 297 mm
Duplex printing *	✓	Custom media length	148 - 432 mm
Maximum resolution *	9600 x 600 DPI	Paper tray media weight	60 - 256 g/m ²
Print speed (black, normal quality, A4/US Letter) *	30 ppm	Multi-Purpose Tray media weight	60 - 256 g/m ²
Print speed (colour, normal quality, A4/US Letter)	30 ppm	Auto Document Feeder (ADF) media weight	45 - 160 g/m ²
Print speed (black, normal quality, A3)	15 ppm	Duplex media weight	60 - 220 g/m ²
Print speed (colour, normal quality, A3)	15 ppm	Media thickness (min)	0.11 mm
Duplex print speed (black, normal quality, A4/US Letter)	26 ppm	Ports & interfaces	
Duplex print speed (colour, normal quality, A4/US Letter)	26 ppm	Direct printing *	✓
Warm-up time	30 s	USB port	✓
Time to first page (black, normal)	6.5 s	USB 2.0 ports quantity	3
Time to first page (colour, normal)	8.3 s	Optional connectivity	Ethernet, Wireless LAN
N-in-1 print function	✓	Network	
N-up printing	2, 4	Wi-Fi *	✗
Barcode printing	✓	Ethernet LAN *	✓
Watermark printing	✓	Cabling technology	10/100/1000Base-T(X)
Economical printing	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Secure printing	✓	Email protocols	POP3, SMTP
Poster printing function	✓	Mobile printing technologies	Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Copying		Performance	
Duplex copying *	✓	Maximum internal memory	3072 MB
Copying *	Colour copying	Card reader integrated	✓
Maximum copy resolution *	600 x 600 DPI	Internal memory *	1536 MB
Copy speed (black, normal quality, A4)	30 cpm	Compatible memory cards	SD, SDHC
Copy speed (colour, normal quality, A4)	30 cpm	Built-in processor	✓
Copy speed (black, normal quality, A3)	15 cpm	Processor family	ARM Cortex-A9
Copy speed (colour, normal quality, A3)	15 cpm	Processor frequency	1200 MHz
Time to first copy (black, normal)	6.5 s	Processor cores	2
Time to first copy (colour, normal)	8.3 s	Sound pressure level (printing)	48.9 dB
Maximum number of copies	999 copies	Sound pressure level (copying)	48.9 dB
Copier resize	25 - 400%	Sound pressure level (quiet mode)	30.8 dB
N-in-1 copy function	✓	Design	
		Product colour *	Black, White
		Market positioning *	Business
		Built-in display *	✓
		Display	TFT
		Display diagonal	17.8 cm (7")

Copying		Design	
N-in-1 copy function (N=)	2, 4	Touchscreen	✓
Copy programming function	✓	Control type	Touch
ID-card copy function	✓	Colour display	✓
Scanning		Power	
Duplex scanning *	✓	Power consumption (printing)	600 W
Scanning *	Colour scanning	Power consumption (copying)	600 W
Optical scanning resolution *	600 x 600 DPI	Power consumption (ready)	70 W
Maximum scan area	297 x 420 mm	Power consumption (sleep)	0.5 W
Scanner type *	Flatbed & ADF scanner	Power consumption (off)	0.1 W
Scan technology	CIS/CCD	Energy Star Typical Electricity Consumption (TEC)	1.39 kWh/week
Scan to	E-mail, FTP, SMB, TWAIN, USB, WIA	AC input voltage	220 - 240 V
Scan speed (colour)	50 ppm	AC input frequency	50 Hz
Scan speed (black)	50 ppm	System requirements	
Duplex scan speed (colour)	16 ppm	Windows operating systems supported	✓
Duplex scan speed (black)	16 ppm	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks	
Image formats supported	JPG, TIFF	Mac operating systems supported	
Document formats supported	PDF, XPS	Linux operating systems supported	
Greyscale levels	256	✓	
Scan drivers	TWAIN, WIA	Operational conditions	
Features		Operating relative humidity (H-H)	10 - 80%
Recommended duty cycle	3000 - 8000 pages per month	Storage temperature (T-T)	-20 - 40 °C
Maximum duty cycle *	15000 pages per month	Operating temperature (T-T)	10 - 32.5 °C
Number of print cartridges *	4	Storage relative humidity (H-H)	10 - 90%
Printing colours *	Black, Cyan, Magenta, Yellow	Operating altitude	0 - 3500 m
Page description languages	OpenXPS, PCL 5c, PCL 6, PCL XL, PostScript 3	Non-operating altitude	0.6 - 15000 m
Printer fonts	Barcode, Bitmap, PCL, Windows	Certificates	
Number of printer fonts	93	Waste Electrical and Electronic Equipment (WEEE) compliance	✓
Optional functions	Fax	Certification	TÜV-GS, CE
Replacement cartridges	TK-8115K, TK-8115C, TK-8115M, TK-8115Y	Sustainability	
Input & output capacity		Sustainability certificates	Blue Angel, ENERGY STAR, EPEAT Silver
Total number of input trays *	3	Weight & dimensions	
Total input capacity *	500 sheets	Width	590 mm
Total output capacity *	250 sheets	Depth	590 mm
Paper tray 1 input capacity	500 sheets	Height	753 mm
Paper tray 2 input capacity	500 sheets	Weight	79 kg
Multi-Purpose tray	✓	Packaging data	
Multi-Purpose tray input capacity	100 sheets	Quantity per pack	1 pc(s)
Paper input type	Cassette, Paper tray	Packaging content	
Auto document feeder (ADF)	✓	Cartridge(s) included	✓
Auto document feeder (ADF) input capacity	50 sheets	Included cartridge capacity (black)	3000 pages
Maximum number of input trays	3	Included cartridge capacity (CMY)	1500 pages
Maximum input capacity	1600 sheets	Cables included	AC
Maximum output capacity	280 sheets	Drivers included	✓
Paper handling		Manual	✓
Maximum ISO A-series paper size *	A3	Power cord included	✓
Maximum print size	297 x 432 mm	Quick installation guide	✓
Paper tray media types *	Plain paper	Technical details	
		Compliance certificates	REACH, RoHS



0632983937549



632983937549

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.