



## APC Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine



**Brand :** APC

**Product code:** SRT6KRMXLIM

**Product name :** Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine

Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine  
APC Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine. UPS topology: Double-conversion (Online), Output power capacity: 6 kVA, Output power: 6000 W. AC outlet types: C13 coupler, C19 coupler, IEC Jumpers, Power plug: Terminal, AC outlets quantity: 13 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 1 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 4U. Compliance certificates: RoHS, Certification: CE, EAC, RCM, VDE, REACH

| Features                                       |                                       | Battery                                          |                          |
|------------------------------------------------|---------------------------------------|--------------------------------------------------|--------------------------|
| UPS topology *                                 | Double-conversion (Online)            | Battery life (max)                               | 5 year(s)                |
| Output power capacity *                        | 6 kVA                                 | Battery recharge time                            | 1 h                      |
| Output power *                                 | 6000 W                                | Hot-swap battery                                 | ✓                        |
| Waveform *                                     | Sine                                  | Automatic battery test                           | ✓                        |
| Input operation voltage (min) *                | 160 V                                 | <b>Design</b>                                    |                          |
| Input operation voltage (max) *                | 275 V                                 | Form factor *                                    | Rackmount                |
| Input frequency *                              | 40 - 70 Hz                            | Rack capacity                                    | 4U                       |
| Output operation voltage (min)                 | 220 V                                 | Product colour *                                 | Black                    |
| Output operation voltage (max)                 | 240 V                                 | Display type                                     | LCD                      |
| Output frequency                               | 50/60 Hz                              | LED indicators                                   | ✓                        |
| Surge energy rating                            | 480 J                                 | International Protection (IP) code               | IP20                     |
| Crest factor                                   | 3:1                                   | <b>Operational conditions</b>                    |                          |
| Emergency Power Off (EPO)                      | ✓                                     | Operating temperature (T-T)                      | 0 - 40 °C                |
| Output voltage Total Harmonic Distortion (THD) | 3%                                    | Storage temperature (T-T)                        | -15 - 45 °C              |
| Noise level                                    | 55 dB                                 | Operating relative humidity (H-H)                | 0 - 95%                  |
| Surge protection                               | ✓                                     | Storage relative humidity (H-H)                  | 0 - 95%                  |
| Audible alarm(s)                               | ✓                                     | Operating altitude                               | 0 - 3000 m               |
| Auto-restart                                   | ✓                                     | Non-operating altitude                           | 0 - 15000 m              |
| Temperature voltage compensation               | ✓                                     | <b>Certificates</b>                              |                          |
| <b>Ports &amp; interfaces</b>                  |                                       | Compliance certificates                          | RoHS                     |
| AC outlet types                                | C13 coupler, C19 coupler, IEC Jumpers | Certification                                    | CE, EAC, RCM, VDE, REACH |
| Power plug                                     | Terminal                              | <b>Weight &amp; dimensions</b>                   |                          |
| AC outlets quantity                            | 13 AC outlet(s)                       | Width                                            | 432 mm                   |
| USB port                                       | ✓                                     | Depth                                            | 719 mm                   |
| USB 2.0 ports quantity                         | 1                                     | Height                                           | 174 mm                   |
| Serial interface                               | ✓                                     | Weight                                           | 60 kg                    |
| Ethernet LAN (RJ-45) ports                     | 1                                     | <b>Packaging data</b>                            |                          |
| Cabling technology                             | 10/100Base-T                          | Package width                                    | 610 mm                   |
| SmartSlot                                      | ✓                                     | Package depth                                    | 960 mm                   |
| <b>Battery</b>                                 |                                       | Package height                                   | 370 mm                   |
| Battery technology                             | Sealed Lead Acid (VRLA)               | Package volume                                   | 67000 cm <sup>3</sup>    |
| Number of batteries supported                  | 1                                     | <b>Logistics data</b>                            |                          |
|                                                |                                       | Products per pallet                              | 6 pc(s)                  |
|                                                |                                       | Harmonized System (HS) code                      | 85078000                 |
|                                                |                                       | Total carbon footprint (kg of CO <sub>2</sub> e) | 55428.62                 |



0731304320838



731304320838

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.