

# ZEUS52E3K 3000VA 2700W Online Tower UPS, IEC

## Product Images



## Short Description

- Output Power Factor 0.9
- ECO Mode for Energy-Saving
- Generator Compatible
- Provides HID compatible USB connection
- Emergency Power Off (EPO) Port
- THDi≤5%

## Description

Introducing the Conceptronic Online Tower UPS, the ultimate power backup solution for your home or office. With an ECO Mode for energy-saving operation and compatibility with generators, this UPS ensures continuous power even during extended outages. Equipped with HID USB communication, you can seamlessly connect and communicate with your devices for enhanced control and monitoring. For added safety during emergencies, the UPS is equipped with an Emergency Power Off (EPO) port, allowing for quick shutdown in critical situations. With its sleek tower design, the Conceptronic Online

Tower UPS fits seamlessly into any environment, providing reliable power backup when you need it most.

## Additional Information

|                         |                                                                                                                                      |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Color                   | Black                                                                                                                                |
| EAN                     | 4015867237847                                                                                                                        |
| Model Number            | ZEUS52E3K                                                                                                                            |
| Protection              | UPS Output Cut off Immediately or Input Fuse / Circuit Breaker Protection                                                            |
| Approval and Compliance | CE, RoHS                                                                                                                             |
| Operating humidity      | 0% RH ~ 90% RH                                                                                                                       |
| Operating temperature   | 0°C ~ 40°C                                                                                                                           |
| Package Contents        | ZEUS52E3K Multilingual quick installation guide<br>Input power cord EU Input power cord UK USB cable RS232 cable                     |
| Recharge time           | 4hr                                                                                                                                  |
| Dimensions (W x D x H)  | 196 x 416 x 342 mm                                                                                                                   |
| Product weight (kg)     | 21.3                                                                                                                                 |
| Alarm                   | Battery Mode, Battery Low, Overload, UPS Fault, Replace Battery, Bypass Mode, Charger Failure /Over Charged, Fan failure, EPO active |
| Battery capacity (mAh)  | 9000                                                                                                                                 |
| Battery capacity (Wh)   | 108                                                                                                                                  |
| Battery voltage         | DC 12V                                                                                                                               |
| Button                  | Power On/Off                                                                                                                         |
| Display                 | Graphic LCD                                                                                                                          |
| Number of ports         | 5                                                                                                                                    |
| Output Power (watt)     | 2700                                                                                                                                 |
| Port Configuration      | IEC C13 x 4, IEC C19 x 1                                                                                                             |
| Power input             | AC 220-240V, 16A max, 50/60Hz                                                                                                        |
| Power Output            | AC 220-240V                                                                                                                          |
| Power rating            | 3000VA                                                                                                                               |

|                |                          |
|----------------|--------------------------|
| Types of ports | IEC                      |
| UPS Type       | Online double conversion |
| Waveform       | Sine wave                |

