

ZEUS51E6K 6000VA 6000W Online Rack/Tower UPS

Product Images



Short Description

- Output power factor 1.0
- ECO mode for energy saving
- Wide Input Range (80V-300V)
- Generator compatible
- Provides HID compatible USB connection
- Emergency Power Off (EPO) port
- Easy battery replacement
- THDi≤5%
- Outlet programmable management
- Battery extendable

Description

The Conceptronic Online Rack/Tower UPS is the ultimate solution for dependable battery backup in both home and office settings. With an output power factor of 1.0, this UPS delivers maximum efficiency and performance. Its ECO mode feature conserves energy, making it an environmentally friendly choice. Designed for generator compatibility, it provides continuous power even during extended outages.

Equipped with a HID-compatible USB connection for seamless device communication and an Emergency Power Off (EPO) port for added safety during emergencies, the Conceptronic Online Rack/Tower UPS offers both convenience and security. The easy battery replacement feature simplifies maintenance, while the programmable outlet management allows you to tailor power distribution to meet your specific needs.

Easy to install and operate, the Conceptronic Online UPS provides a reliable and efficient way to protect your systems from power surges and failures, ensuring the uninterrupted operation of your critical equipment. The included rackmount ears support both rack mounting and tower installation, offering flexibility in setup.

Additional Information

Harmonized System (HS) code	850440
Customs product code (TARIC)	8504406090
Protection	UPS Output Cut off Immediately or Input Fuse / Circuit Breaker Protection
Approval and Compliance	CE, RoHS
Operating humidity	0% RH ~ 90% RH
Operating temperature	0°C ~ 40°C
Recharge time	4hr
Dimensions (W x D x H)	438 x 680 x 261 mm
Product weight (kg)	59.4
Color	Black
EAN	4015867237816
Model Number	ZEUS51E6K
Alarm	Battery Mode, Battery Low, Overload, UPS Fault, Replace Battery, Bypass Mode, Charger Failure /Over Charged, Fan failure, EPO active
Battery capacity (mAh)	7000
Battery capacity (Wh)	84
Battery voltage	192V
Switches/Buttons	Power On/Off, Enter, ESC
Display	Graphic LCD
Number of battery	16
Power input	AC 220-240V, 50/60Hz
Power Output	AC 220-240V
Power rating	6000VA
UPS Type	Online double conversion
Waveform	Sine wave

