



Product family: Color LaserJet Enterprise Flow **Product code:** 3WT91A#B19

- Front-facing USB printing
- Print, copy, scan and fax
- Up to 46 ppm
- Up to 1200 x 1200 dpi

Color LaserJet Enterprise Flow MFP M776z

Expect brilliant colour prints from advanced MFPs, equipped with JetIntelligence technology. Offering the world's most secure printing ^[1] and a wide range of paper handling features, this is printing that helps save time and simplifies workflows.

The image displays two perspectives of the HP Color LaserJet Enterprise M750dn. The top view is a front-facing image showing the printer's control panel with a color touchscreen and a keyboard. The bottom view is a side profile of the same printer, highlighting its four large paper drawers at the base and the paper input/output paths. The HP logo is visible on the front panel of both views.

Publication date: 12-APR-2026. Prints or copies of Information are only valid on the printed Publication date

Printing		Design	
Watermark printing	✓	Control type	Buttons, Touch
Secure printing	✓	Colour display	✓
Copying		Power	
Duplex copying *	✓	Power consumption (average operating)	900 W
Copying *	Colour copying	Power consumption (PowerSave)	0.8 W
Maximum copy resolution *	600 x 600 DPI	Power consumption (printing)	900 W
Copy speed (black, normal quality, A4)	46 cpm	Power consumption (ready)	100 W
Copy speed (colour, normal quality, A4)	46 cpm	Power consumption (sleep)	0.8 W
Copy speed (black, normal quality, A3)	26 cpm	Power consumption (off)	0.07 W
Copy speed (colour, normal quality, A3)	26 cpm	Energy Star Typical Electricity Consumption (TEC)	2.47 kWh/week
Time to first copy (black, normal)	5.6 s	AC input voltage	220 - 240 V
Time to first copy (colour, normal)	7.7 s	AC input frequency	50/60 Hz
Maximum number of copies	9999 copies	Brand-specific features	
Copier resize	25 - 400%	HP Auto-On/Auto-Off	✓
N-in-1 copy function	✓	HP Dynamic security	✓
Book copy function	✓	HP Security tools	Management security: SNMPv3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in
ID-card copy function	✓		
Auto fit function	✓		
Scanning			
Duplex scanning *	✓	HP GTIN (EAN/UPC) with options	(ABT) 193424432196; (ABY) 193424432202; (ACQ) 193424432219; (B13) 193424432226; (B19) 193424432233; (BAZ) 193424432257
Scanning *	Colour scanning		
Optical scanning resolution *	600 x 600 DPI		
Maximum scan resolution	600 x 600 DPI		
Maximum scan area	297 x 432 mm	HP GTIN (EAN/UPC)	193424432196, 193424432202, 193424432219, 193424432226, 193424432233, 193424432257
Scanner type *	Flatbed scanner		
Scan technology	CIS/CCD	System requirements	
Scan to	E-mail, Network folder, USB, TWAIN	Windows operating systems supported	Windows 7 Ultimate x64, Windows 7 Ultimate, Windows 7 Starter x64, Windows 7 Starter, Windows 7 x64, Windows 7, Windows 8 x64, Windows 8, Windows 8.1 x64, Windows 8.1, Windows 10 x64, Windows 10
Scan speed (colour)	120 ppm		
Scan speed (black)	120 ppm	Mac operating systems supported	Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, MacOS
Image formats supported	JPEG, MTIFF, TIFF		
Document formats supported	CSV, HTML, PDF, RTF, UNICODE, XPS	Other operating systems supported	Android, iOS
Input colour depth	48 bit		
Greyscale levels	256	Operational conditions	
Scan drivers	TWAIN	Operating relative humidity (H-H)	10 - 80%
Fax		Recommended humidity operating range	30 - 70%
Faxing *	Colour faxing	Recommended operating temperature range (T-T)	15 - 27 °C
Fax resolution (black)	300 x 300 DPI	Storage temperature (T-T)	-20 - 40 °C
Fax transmission speed	6 sec/page	Operating temperature (T-T)	10 - 32.5 °C
Modem speed	33.6 Kbit/s		
Fax memory	500 pages		
Auto-redialing	✓		
Speed dialling	✓		
Fax forwarding	✓		
Fax delayed sending	✗		
Auto reduction	✓		
Features			
Recommended duty cycle	0 - 40000 pages per month		
Maximum duty cycle *	200000 pages per month		
Duplex functions *	Print		
Digital sender	✓		
Number of print cartridges *	4		
Printing colours *	Black, Cyan, Magenta, Yellow		
Page description languages	PostScript 3, PDF 1.7, PCL 6		

Features		Certificates	
Printer fonts	Scalable, TrueType, Windows, PCL, PostScript, Barcode	Certification	CISPR 22:2008 (International) - Class A, CISPR32:2012 (International) - Class A, EN 55032:2012 (EU) - Class A, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010, EMC Directive 2014/30/EU. Other EMC approvals as required by individual countries.
All-In-One-multitasking	✓		
Country of origin	Japan		
Replacement cartridges	W2010A HP 659A Black LaserJet Toner Cartridge (16,000 pages); W2011A HP 659A Cyan LaserJet Toner Cartridge (13,000 pages); W2012A HP 659A Yellow LaserJet Toner Cartridge (13,000 pages); W2013A HP 659A Magenta LaserJet Toner Cartridge (13,000 pages); W2010X HP 659X Black LaserJet Toner Cartridge (34,000 pages); W2011X HP 659X Cyan LaserJet Toner Cartridge (29,000 pages); W2012X HP 659X Yellow LaserJet Toner Cartridge (29,000 pages); W2013X HP 659X Magenta LaserJet Toner Cartridge (29,000 pages); W2004A HP 660A Original LaserJet Imaging Drum (65,000 pages, universal for all 4 colours)		
HP segment	Business		
Input & output capacity			
Total number of input trays *	5		
Total input capacity *	2300 sheets		
Total output capacity *	500 sheets		
Paper tray 1 input capacity	100 sheets		
Paper tray 2 input capacity	550 sheets		
Multi-Purpose tray	✓		
Multi-Purpose tray input capacity	100 sheets		
Auto document feeder (ADF)	✓		
Auto document feeder (ADF) input capacity	200 sheets		
Maximum number of input trays	5		
Maximum input capacity	2300 sheets		
Maximum output capacity	500 sheets		
Paper handling			
Maximum ISO A-series paper size *	A3		
Maximum print size	302 x 454.2 mm		
Paper tray media types *	Plain paper, Glossy paper, Recycled paper, Envelopes, Card stock, Labels, Transparencies, Heavy paper, Lightweight paper		
ISO A-series sizes (A0...A9) *	A3, A4, A5, A6		
ISO B-series sizes (B0...B9)	B5		
ISO C-series sizes (C0...C9)	C5, C6		
Non-ISO print media sizes	Oficio, 16K		
JIS B-series sizes (B0...B9)	B4, B5, B6		
Envelopes sizes	B5, C5, C6, DL		
Custom media width	64 - 320 mm		
Custom media length	127 - 457.2 mm		
Paper tray media weight	60 - 256 g/m²		
Multi-Purpose Tray media weight	60 - 300 g/m²		
Envelope feeder	No		
Ports & interfaces			
Direct printing *	✓		
USB port	✓		
USB 2.0 ports quantity	4		
Network			
Wi-Fi *	✓		
Ethernet LAN *	✓		

Sustainability	
Sustainability compliance	✓
Sustainability certificates	Blue Angel, ENERGY STAR, EPEAT Gold
Sustainable technologies and materials	Mercury free
Doesn't contain	Mercury
Carbon footprint	
Total carbon footprint (kg of CO2e)	980
Carbon emissions, manufacturing (kg of CO2e)	549
Carbon emissions, logistics (kg of CO2e)	34
Total carbon emissions, w/o use phase (kg of CO2e)	380
Weight & dimensions	
Width	585 mm
Depth	712 mm
Height	1160 mm
Weight	115.5 kg
Packaging data	
Package width	856 mm
Package depth	760 mm
Package height	1556 mm
Package weight	126.5 kg
Packaging content	
Cables included	AC
Logistics data	
Harmonized System (HS) code	84433100
Pallet gross weight	126.5 kg
Layers per pallet	1 pc(s)
Products per pallet	1 pc(s)
Technical details	
Box contents	HP Color LaserJet Enterprise Flow MFP M776z printer; HP Black Original LaserJet Toner Cartridge (16,000 pages); HP Cyan, Magenta and Yellow Original LaserJet Toner Cartridges (13,000 pages each); 4 HP Original LaserJet Imaging Drums (65,000 pages each colour); Getting started Guide; 1 Power cord
Master (outer) cases per pallet layer	1 pc(s)
Compliance certificates	CECP, GS mark, CCC, cUL, UL, CE, BSMI
General Product Safety Regulation (GPSR) URL	https://support.hp.com/gb-en/product/setup-user-guides/hp-color-laserjet-enterprise-mfp-m776-series/model/26058336?sku=3WT91A ; https://h10032.www1.hp.com/ctg/Manual/c06362773.pdf
Other features	
Number of users	20 user(s)
Custom media sizes	100 sheet multipurpose Tray 1: 64 x 127 to 320 x 457.2 mm; 550 sheet input Tray 2: 148 x 148 to 297 x 431.8 mm; 1 x 550 and 2 x 550 tray and stand: 148 x 148 to 320 x 457.2 mm
Pallet dimensions (W x D x H)	856 x 760 x 1556 mm
Recommended system requirements	2 GB available hard disk space; Internet connection; USB port; Internet browser. 2 GB available hard drive space; Internet connection or USB port.

Network		Other features	
Cabling technology	10/100/1000Base-T(X)		Windows Client OS (32/64 bit): Win10, Win8.1, Win7 Starter Edition SP1, UPD Win7 Ultimate; Mobile OS: iOS, Android; Apple macOS High Sierra v10.13, Apple macOS Mojave v10.14, Mac: Apple macOS Catalina v10.15; Discrete PCL6 Printer Driver: For more information on the supported operating systems go to http://support.hp.com , Enter your product name and search, Click on User Guides and enter your product name and search for User Guide, Search for your (Product Name) User Guide, Search for the Supported Operating Systems section; UPD PCL6 / PS Printer Drivers: For more information on the supported operating systems go to http://www.support.hp.com , Enter your product name and search, Click on User Guides and enter your product name and search for User Guide, Search for your (Product Name) User Guide, Search for the Supported Operating Systems section; UPD PCL6 / PS Printer Drivers, Supported Operating systems, For more information on the supported operating systems see http://www.hp.com/go/upd
Ethernet LAN data rates	10,100,1000 Mbit/s	Compatible operating systems	
Bluetooth	✓		
		Acoustic power emissions (ready)	49 dB
		Acoustic pressure emissions bystander (ready)	32 dB
		Typical electricity consumption (TEC) number	Blue Angel: 2.470 kWh/Week; Energy Star 3.0: 0.734 kWh/Week
		UNSPSC-code	43212110
		Processor frequency	1.2 GHz
		Electromagnetic compatibility	CISPR 22:2008 (International) - Class A, CISPR32:2012 (International) - Class A, EN 55032:2012 (EU) - Class A, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010, EMC Directive 2014/30/EU. Other EMC approvals as required by individual countries.



0193424432233



193424432233

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-APR-2026. Prints or copies of Information are only valid on the printed Publication date