



Product code: DELL-P2422HWOS

Product name : P2422H WOST



- 60.5cm (23.8") Full HD 1920 x 1080 LED IPS
- 8ms, 16:9, 250cd/m², 1000:1
- USB, VGA, HDMI, DisplayPort

60.5cm (23.8") Full HD 1920 x 1080 LED IPS, 16:9, 250cd/m², 16.7M, 8ms, 178°/178°, 1000:1

DELL P Series P2422H WOST computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black:

Stay productive, no matter where you work. Reduce harmful blue light with this sleek 23.8" FHD monitor featuring ComfortView Plus technology.

DELL P Series P2422H_WOST. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black



Display	
Display diagonal *	60.5 cm (23.8")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
Backlight type	LED
Touchscreen *	✗
Display brightness (typical)	250 cd/m²
Response time *	8 ms
Anti-glare screen	✓
Screen shape *	Flat
Supported graphics resolutions	1920 x 1080 (HD 1080)
Supported video modes	480p, 576p, 720p, 1080i, 1080p
Aspect ratio	16:9
Contrast ratio (typical) *	1000:1
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Response time (fast)	5 ms
Pixel pitch	0.2745 x 0.2745 mm
Pixel density	93 ppi
Horizontal scan range	30 - 83 kHz
Vertical scan range	50 - 76 Hz
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Viewable size diagonal	60.5 cm
Display diagonal (metric)	60.47 cm
Ergonomics	
Height adjustment *	✗
Pivot	✗
Swivelling	✗
Tilt adjustment	✗
Tilt angle range	0 - 0°
On Screen Display (OSD)	✓
Plug and Play	✓
LED indicators	Power
Power	
Energy efficiency class (SDR) *	C
Energy efficiency class (HDR) *	Not available
Energy consumption (SDR) per 1000 hours *	12 kWh
Power consumption (typical) *	12 W
Power consumption (standby) *	0.3 W
Power consumption (max)	48 W
Power consumption (off)	0.2 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m

Display		Operational conditions	
High Dynamic Range (HDR) supported	✗	Non-operating altitude	0 - 12192 m
Colour depth	6 bit	Weight & dimensions	
sRGB coverage (typical)	99%	Width (with stand)	537.8 mm
Performance		Width (without stand)	537.8 mm
Flicker-free technology	✓	Depth (without stand)	52.1 mm
Low Blue Light technology	✓	Height (without stand)	318.5 mm
Multimedia		Weight (without stand)	3.39 kg
Built-in speaker(s) *	✗	Bezel width (side)	5.38 mm
Built-in camera *	✗	Bezel width (top)	5.38 mm
Design		Bezel width (bottom)	1.67 cm
Market positioning *	Business	Packaging content	
Product colour *	Black	Cables included	AC, DisplayPort, HDMI, USB, VGA
Front bezel colour	Black	Quick start guide	✓
Ports & interfaces		Sustainability	
Built-in USB hub *	✓	Sustainability certificates	ENERGY STAR, EPEAT Gold
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)	Doesn't contain	PVC/BFR
USB upstream port type	USB Type-B	Carbon footprint	
Number of upstream ports	1	Total carbon footprint (kg of CO2e)	464
USB Type-A downstream ports quantity	4	Total carbon emissions, standard deviation (kg of CO2e)	96
VGA (D-Sub) ports quantity	1	Carbon emissions, manufacturing (kg of CO2e)	320.09
HDMI *	✓	Carbon emissions, logistics (kg of CO2e)	30.6
HDMI ports quantity	1	Carbon emissions, energy usage (kg of CO2e)	111
HDMI version	1.4	Carbon emissions, end-of-life (kg of CO2e)	1.69
DisplayPorts quantity	1	PAIA version	1.2.15, 2021
DisplayPort version	1.2	Other features	
Headphone out *	✗	Heavy metals free	Hg (mercury)
HDCP	✓	Compliance certificates	RoHS
AC (power) in	✓	Logistics data	
Network		Harmonized System (HS) code	85285210
Wi-Fi	✗		
Ergonomics			
VESA mounting *	✓		
Panel mounting interface	100 x 100 mm		
Cable lock slot *	✗		



5397184505182



3523210099437

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.