




FCS-3065 Version: 1

! Power supply unit is to be ordered separately.

HUBBLE Fixed Dome IP Network Camera, 5-Megapixel, 802.3af PoE, Vandalproof



Key Features

- Built-in Micro SDHC/SDXC card slot for local storage
- 5-Megapixel high-definition resolution
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Vandal-proof IK08-rated housing
- Video compression: H.264, MJPEG
- Power support: PoE (IEEE 802.3af)
- Free surveillance and CMS (Central Management System) software packages with 64-channel license

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

IEEE 802.1X Network Access Control

TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

Image Sensor:

5-Megapixel 1/3.2" Progressive Scan CMOS

Lens:

Fixed focal, Fixed iris, Fixed focus, f1.9mm, F2.8

Port:

1 x RJ-45 10/100 Mbps PoE port

1 x MicroSDHC/ MicroSDXC card slot

Button/Knob:

Reset Button

Indicator:

Power

Shutter Time:

1/5 ~ 1/10,000 sec

Angle of View:

126.9° (overview area), 77.4° (high detail area)

Pan/Tilt/Zoom:

Digital Zoom to very high detail available on Software

Video Compression:

H.264 / MJPEG

Resolution:

5M(2592 x 1944)

Output Video Format:

RAW

Power Input:

802.3af PoE

Power Consumption:

PoE Class 1 (IEEE802.3af) / 2.91 W

Data Rate:

10/100Mbps

Storage Capacity:

SD/MicroSD memory card of up to 64GB

Features

General:

Backup: MicroSDHC /MicroSDXC card slot for local storage

Video:

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure

- AGC/AWB/AES

- Back Light Compensation (BLC)

- Wide Dynamic Range (WDR), Basic WDR (74 dB)

- 2D Noise Reduction (2DNR)

- Streaming: Up to 2 video streams

Performance

Frame Rate (fps):

15 fps at 2592 x 1944; 15 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

Minimum illumination:

Color: 0.1 lux at F2.8

Environment

Operating Temperature (°C):

Operating: -10°C ~ 50°C

Operating Humidity (Non-condensing):

Operating: 10% ~ 85%

Installation:

Wall/Ceiling Mount

Physical Specifications

Dimensions (W x D x H mm):

110 x 58 x 110

Weight (g):

191 g

Approval and Compliance

EMI/EMS:

CE, RoHS, FCC, ONVIF, IK08

Environmental Test:


Vandal Resistant IK08-protected

Others

Supported Browsers:

Microsoft Windows 8/7/Vista/XP

Diagram



Order Information

FCS-3065

Package Contents

FCS-3065
Screw Kit
Quick Installation Guide
Resource CD (User Manual, Utility, QIG)

Optional Accessory



CAS-2316
Wall Mount Bracket

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.