



TP-Link Omada SG3452XMPP network switch Managed L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Brand : TP-Link

Product family: Omada

Product code: SG3452XMPP



Product name : SG3452XMPP

- 4x 10 Gbps SFP+ slots
- 8x Gigabit 802.af/at/bt PoE++ ports (Max 90 W PoE budget for each port)
- 40x Gigabit 802.3af/at PoE+ ports (Max 30 W budget for each port)
- 750 W total PoE budget*
- Centralized cloud management via the web or the Omada app†
- Standalone management via web, CLI, SNMP, and RMON

40x 10/100/1000 Mbps RJ45 PoE+, 4x 10G SFP+ Slots, 1x RJ45, 1x Micro-USB, 176 Gbps, MAC 16 K, 440 x 330 x 44 mm

TP-Link Omada SG3452XMPP. Switch type: Managed, Switch layer: L2+. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48, Console port: RJ-45/Micro-USB. MAC address table: 16000 entries, Switching capacity: 176 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE.... Power connector: AC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U




Management features		Security	
Switch type *	Managed	BPDU filtering/protection	✓
Switch layer	L2+	IP-MAC-Port binding	✓
Quality of Service (QoS) support	✓	Authentication	Auto VLAN, Guest VLAN
Web-based management	✓	Multicast features	
Cloud-managed	✓	Multicast support	✓
ARP inspection	✓	Design	
Configuring Location Settings (CLI)	✓	Rack mounting *	✓
System event log	✓	Form factor	1U
Ports & interfaces		Product colour	Black
Basic switching RJ-45 Ethernet ports quantity *	48	Reset button	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	LED indicators	✓
SFP+ module slots quantity	4	Number of fans	3 fan(s)
Console port	RJ-45/Micro-USB	Power	
Power connector	AC-in jack	Power source *	AC
Network		Power supply included *	✓
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z	AC input voltage	100 - 240 V
		AC input frequency	50/60 Hz
		Power consumption (max)	635.7 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✓
10G support *	✓	Power over Ethernet plus (PoE+) ports quantity	40
Port mirroring	✓	Power over Ethernet 4PPoE (PoE++) ports quantity	8
Flow control support	✓	Power over Ethernet (PoE) power per port	30 W
Link aggregation	✓		
Broadcast storm control	✓		
Rate limiting	✓		

Network		Power over Ethernet (PoE)	
Spanning tree protocol	✓	Total Power over Ethernet (PoE) budget	750 W
Head-of-line (HOL) blocking	✓	Operational conditions	
VLAN support	✓	Operating temperature (T-T)	0 - 40 °C
Data transmission		Storage temperature (T-T)	-40 - 70 °C
Switching capacity *	176 Gbit/s	Operating relative humidity (H-H)	10 - 90%
Forwarding rate	130.9 Mpps	Storage relative humidity (H-H)	5 - 90%
MAC address table *	16000 entries	Heat dissipation	2169.2 BTU/h
Store-and-forward	✓	Weight & dimensions	
Jumbo frames support	✓	Width	440 mm
Jumbo frames	9000	Depth	330 mm
Packet buffer memory	12 MB	Height	44 mm
Security		Packaging content	
DHCP features	DHCP client, DHCP relay, DHCP server	Cables included	AC
Access Control List (ACL)	✓	Quick start guide	✓
IGMP snooping	✓	Certificates	
MAC address filtering	✓	Certification	CE, FCC, RoHS
Static port security	✓		
SSH/SSL support	✓		



8885020620870



8885020620887



0810142820417



810142820417

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.