

Philips P Line 32:9 SuperWide curved LCD display 499P9H/00

Brand : Philips

Product family: P Line

Product code: 499P9H/00

Product name : 32:9
SuperWide curved LCD display
499P9H/00



Monitor 499P9H 32:9 SuperWide curved LCD display

Philips P Line 32:9 SuperWide curved LCD display 499P9H/00:

Our award-winning 49" curved 32:9 SuperWide display is like two full-size high-performance monitors in one. Productivity-enhancing features like USB-C and pop-up webcam with Windows Hello deliver the performance and convenience you expect.

Philips P Line 32:9 SuperWide curved LCD display 499P9H/00. Display diagonal: 124 cm (48.8"), Display resolution: 5120 x 1440 pixels, HD type: UltraWide Dual Quad HD, Display technology: LCD, Display surface: Matt, Response time: 5 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ergonomics	
Display diagonal *	124 cm (48.8")	VESA mounting *	✓
Display resolution *	5120 x 1440 pixels	Panel mounting interface	100 x 100 mm
HD type *	UltraWide Dual Quad HD	Cable lock slot *	✓
Native aspect ratio *	32:9	Cable lock slot type	Kensington
Display technology *	LCD	Height adjustment *	✓
Panel type *	VA	Adjustable height (max)	13 cm
Backlight type	W-LED	Swivelling	✓
Touchscreen *	✗	Swivel angle range	-20 - 20°
Display brightness (typical)	450 cd/m²	Tilt adjustment	✓
Response time *	5 ms	Tilt angle range	-5 - 15°
Display surface	Matt	On Screen Display (OSD)	✓
Anti-glare screen	✓	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Screen shape *	Curved		
Screen curvature rating	1800R		
Supported graphics resolutions	2560 x 1440, 3440 x 1440, 5120 x 1440	Number of OSD languages	21
Aspect ratio	32:9	Plug and Play	✓
Contrast ratio (typical) *	3000:1	LED indicators	Operation, Stand-by
Contrast ratio (dynamic)	80000000:1	Power	
Dynamic contrast ratio marketing name	SmartContrast	Energy efficiency class (SDR) *	G
Maximum refresh rate *	70 Hz	Energy efficiency class (HDR) *	G
Viewing angle, horizontal	178°	Energy consumption (SDR) per 1000 hours *	52 kWh
Viewing angle, vertical	178°	Energy consumption (HDR) per 1000 hours *	94 kWh
Display number of colours *	16.7 million colours	Power consumption (typical) *	41.25 W
Pixel pitch	0.233 x 0.233 mm	Power consumption (standby) *	0.3 W
Pixel density	109 ppi		
Horizontal scan range	30 - 230 kHz		
Vertical scan range	48 - 70 Hz		

Display		Power	
Viewable size, horizontal	119.3 cm	Power consumption (off)	0 W
Viewable size, vertical	33.6 cm	Power consumption (PowerSave)	43.3 W
Digital horizontal frequency	30 - 230 kHz	AC input voltage	100 - 240 V
Digital vertical frequency	48 - 70 Hz	AC input frequency	50 - 60 Hz
Sync-on-green (SOG)	✓	Power supply type	Internal
Display diagonal (metric)	124 cm	Energy efficiency scale	A to G
High Dynamic Range (HDR) supported	✓	Operational conditions	
High Dynamic Range (HDR) technology	DisplayHDR 400	Operating temperature (T-T)	0 - 40 °C
DDC/CI	✓	Storage temperature (T-T)	-20 - 60 °C
Haze rate	25%	Operating relative humidity (H-H)	20 - 80%
Surface hardness	2H	Operating altitude	0 - 3658 m
Colour depth	8 bit	Non-operating altitude	0 - 12192 m
Colour gamut standard	sRGB	Weight & dimensions	
Colour gamut	103%	Width (with stand)	1194 mm
sRGB coverage (typical)	121%	Depth (with stand)	303 mm
NTSC coverage (typical)	100%	Height (with stand)	568 mm
Adobe RGB coverage	91%	Weight (with stand)	15.3 kg
Screen curvature	180 cm	Width (without stand)	1194 mm
3D	✗	Depth (without stand)	156 mm
Separate H/V sync	✓	Height (without stand)	369 mm
DCI-P3 coverage	91%	Weight (without stand)	11 kg
Display sRGB	✓	Packaging data	
Performance		Package width	1308 mm
NVIDIA G-SYNC *	✗	Package depth	553 mm
AMD FreeSync *	✗	Package height	384 mm
VESA Adaptive Sync support	✓	Package weight	21.5 kg
Component video sync	Separate Sync	Package type	Box
Flicker-free technology	✓	Packaging content	
Low Blue Light technology	✓	Stand included	✓
Multimedia		Cables included	HDMI, DisplayPort, USB Type-A to USB Type-B, USB Type-C to USB Type-C, USB Type-C to USB Type-A, AC
Number of speakers	2	Manual	✓
RMS rated power	10 W	Bundled software	SmartControl
Built-in speaker(s) *	✓	Sustainability	
Megapixel (approx.)	2 MP	Sustainability certificates	ENERGY STAR, TCO
Built-in microphone	✓	Doesn't contain	PVC/BFR, Mercury
Built-in camera *	✓	Other features	
Design		HBR3 support	✓
Market positioning *	Home	On/off switch	✓
Product colour *	Black	USB Power Delivery revision	3.0
Front bezel colour	Black	TV tuner integrated	✗
Feet colour	Black	Picture-by-Picture (PbP)	✓
Ports & interfaces		Exterior finish type	Textured
Built-in USB hub *	✓	Heavy metals free	Hg (mercury)
USB hub version	3.2 Gen 1 (3.1 Gen 1)	EasyRead mode	✓
USB upstream port type	USB Type-C	LowBlue mode	✓
Number of upstream ports	1	Philips SmartUniformity	97 - 102%
USB Type-A downstream ports quantity	3	Compliance certificates	RoHS, WEEE
USB Type-C DisplayPort Alternate Mode	✓	Picture enhancement	SmartImage
USB Power Delivery (USB PD)	✓	MultiView	PBP (2 x devices)
USB Power Delivery up to	90 W	Regulatory Approvals	CCC; CECP; KCC; PSE; VCCI; J-MOSS; BSMI; RCM; CE Mark; FCC Class B; PSB; E-standby; UKRAINIAN; ICES-003; CU-EAC; cETLus; TUV/GS; TUV Ergo; MEPS; CEL; KC; CB
DVI port	✗		
HDMI *	✓		
HDMI ports quantity	2	Delta E	2

Ports & interfaces		Other features	
HDMI version	2.0b	Mean time between failures (MTBF)	70000 h
DisplayPorts quantity	1	Ethernet LAN data rates	10,100,1000 Mbit/s
DisplayPort version	1.4	Ethernet LAN (RJ-45) ports	1
Audio input	✗	Wake-on-LAN	✓
Headphone out *	✓	Supplied AC adapter type	5120 x 1440 @ 60 Hz
Headphone outputs	1	Certification	CCC, CECF, KCC, PSE, VCCI, J-MOSS, BSMI, RCM, CE Mark, FCC Class B, PSB, E-standby, UKRAINIAN, ICES-003, CU-EAC, cETLus, TUV/GS, TUV Ergo, SEMKO, MEPS, CEL, KC, CB
HDCP	✓		
HDCP version	1.4/2.2		
AC (power) in	✓		
Network		Recycling data	
Ethernet LAN	✓	Total amount of recyclable materials	85%
		Recyclable packaging material	100%
		Post-consumer recycled plastic	85%
		Logistics data	
		Harmonized System (HS) code	85285210



8712581753719

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.