



Canon i-SENSYS LBP325x 600 x 600 DPI A4

Brand : Canon

Product family: i-SENSYS

Product code: 3515C004

Product name : LBP325x

LCD, A4, 43 ppm, 36 ipm, 600 x 600 dpi, 69 dB, 1 GB, 60-120g/m², USB, LAN

[Canon i-SENSYS LBP325x 600 x 600 DPI A4:](#)

Canon i-SENSYS LBP325x

Get superior print speeds and flexible media handling with this compact black and white single-function laser printer

Compact and efficient single-function mono printer

Modernise your business with this compact black and white laser printer. With rapid print speeds of 43ppm for A4 and 65ppm for A5, the i-SENSYS LBP325x also has the option of three additional paper cassettes – ideal for heavy workloads.

High-speed printing

Accelerate your business's productivity with superior print speeds of 43ppm and 65ppm for A4 and A5 respectively.

Small footprint

Maximise space in a smaller office with an efficient and compact single-function printer.

Easy operation

Take control with a user-friendly and intuitive 5-Line LCD display



Printing		Network	
Duplex printing mode	Auto	Wi-Fi *	✗
Colour *	✗	Ethernet LAN *	✓
Print technology *	Laser	Cabling technology	10/100/1000Base-T(X)
Duplex printing *	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Maximum resolution *	600 x 600 DPI	Mobile printing technologies	Apple AirPrint, Canon PRINT Business, Google Cloud Print, Mopria Print Service
Print speed (black, normal quality, A4/US Letter) *	43 ppm	Performance	
Warm-up time	30 s	Internal memory *	1024 MB
Time to first page (black, normal)	5.7 s	Built-in processor	✓
Print margins (top, bottom, right, left)	5 mm	Processor frequency	528 MHz
Secure printing	✓	Sound pressure level (printing)	69 dB
Features		Design	
Maximum duty cycle *	150000 pages per month	Market positioning *	Business
Recommended duty cycle	2000 - 7500 pages per month	Product colour *	White
Printing colours *	Black, White	Built-in display *	✓
Page description languages *	PCL 5e, PCL 6, PostScript 3, UFR II	Display	LCD
Number of printer fonts	241	Display number of lines	5 lines
Input & output capacity		Power	
Total number of input trays *	1	Power consumption (printing) *	600 W
Total input capacity *	550 sheets	Power consumption (max)	1380 W
Total output capacity *	150 sheets	Power consumption (standby)	10.1 W
Paper input type	Cassette, Paper tray	Power consumption (PowerSave)	1.2 W
Multi-Purpose tray	✓	Energy Star Typical Electricity Consumption (TEC)	1.5 kWh/week
Multi-Purpose tray input capacity	100 sheets	AC input voltage	220 - 240 V
Maximum number of input trays	4	AC input frequency	50 - 60 Hz
Maximum input capacity	2300 sheets	System requirements	
Paper handling		Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista
Maximum ISO A-series paper size *	A4		

Paper handling		System requirements	
Paper tray media types *	Bond paper, Envelopes, Heavy paper, Labels, Plain paper, Postcard, Recycled paper	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.9 Mavericks
Multi-purpose tray media types	Envelopes		
ISO A-series sizes (A0...A9) *	A4, A5, A6	Linux operating systems supported	✓
ISO B-series sizes (B0...B9)	B5		
Envelopes sizes	C5, Com-10, DL, Monarch	Server operating systems supported	Windows Server 2003, Windows Server 2003 R2, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Custom media width	105 - 216 mm		
Custom media length	148 - 355.6 mm		
Paper tray media weight	60 - 120 g/m ²		
Multi-Purpose Tray media weight	60 - 199 g/m ²		
Duplex media weight	60 - 120 g/m ²		
Ports & interfaces		Operational conditions	
USB port *	✓	Operating temperature (T-T)	10 - 30 °C
USB 2.0 ports quantity	1	Operating relative humidity (H-H)	20 - 80%
Network		Weight & dimensions	
Network ready	✓	Width	417 mm
		Depth	376 mm
		Height	330 mm
		Weight	11.5 kg
		Logistics data	
		Harmonized System (HS) code	84433210
		Other features	
		Printer management	Department ID Management, Remote User Interface, iW Management Console, eMaintenance, uniFLOW
		Acoustic pressure emissions	54 dB



4549292133851

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.