



TP-Link 5G Outdoor Router Build-In 5G Modem 5G wireless router 2.5 Gigabit Ethernet White

Brand : TP-Link

Product code: NE200-OUTDOOR

Product name : 5G Outdoor Router Build-In 5G Modem 5G wireless router 2.5 Gigabit Ethernet White

5G, LTE-Advanced Cat19, IP66, 2.5GE Port, PoE

TP-Link 5G Outdoor Router Build-In 5G Modem 5G wireless router 2.5 Gigabit Ethernet White:

Unrivalled 5G Speed: Experience blazing-fast download speeds up to 4.67 Gbps with 5G technology.

LTE-Advanced Cat19: Offers up to 1.6 Gbps mobile download speeds for unparalleled performance.

Durable outdoor enclosure: Robust outdoor connectivity and reliability with IP66 weatherproof protection and $\pm 6\text{kV}$ lightning protection & $\pm 15\text{kV}$ ESD protection.

2.5GE Port for Internet access: The 2.5GE port provides outstanding speed, ensuring an enhanced networking experience.

PoE Power Supply: Supports 802.3at and passive PoE, enabling easy deployment.

Multiple mounting installation: Install easily anywhere with pole, wall, or window mounting for flexible, convenient use.

Plug and Play: Plug in a SIM card to get instant internet access anywhere.



WAN connection		Protocols	
Ethernet WAN *	✓	Universal Plug and Play (UPnP)	✓
SIM card slot *	✓	Design	
3G/4G USB modem compatibility *	✓	Product colour	White
Network		International Protection (IP) code	IP67
Ethernet LAN *	✓	Certificates	
Ethernet LAN interface type *	2.5 Gigabit Ethernet	Compliance certificates	CE, RoHS
Ethernet LAN data rates	2500 Mbit/s	Packaging content	
Dynamic DNS (DDNS)	✓	Cables included	AC, LAN (RJ-45)
VPN server	PPTP VPN, IPSec VPN, OpenVPN	Mounting kit	✓
Mobile network		Quick installation guide	✓
Mobile network generation	5G	Antenna	
3G standards	DC-HSPA+, HSPA, UMTS	Antenna design *	Internal
4G standard	LTE-FDD	Power	
5G standard	NR	Power source type *	AC, PoE
5G bands supported	700,800,850,900,1800,2100,2300,2500,2600,3500,3700 MHz	Power over Ethernet (PoE)	✓
SIM card type	NanoSIM	Power over Ethernet (PoE) voltage	57 V
Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports *	1	Operating temperature (T-T)	-30 - 50 °C
Security		Storage temperature (T-T)	-30 - 70 °C
Firewall	✓	Operating relative humidity (H-H)	5 - 95%
Firewall security	DoS, IPv4 SPI Firewall, IPv6 Firewall, IP and MAC Address Binding	Weight & dimensions	
Protocols		Width	183 mm
DHCP client	✓	Depth	110 mm
DHCP server	✓	Height	36 mm



1210002601559

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.